

Revision Number: 002.0

Issue date: 08/01/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LePage® Carpenter's Glue

IDH number:

530539

Product type:

Adhesive

Restriction of Use:

None identified

Region:

Canada

Company address:

Henkel Canada Corporation

Contact information:

Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3

WARNING:

Telephone: +1 (905) 814-6511

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.	

HAZARD CLASS	HAZARD CATEGORY
REPRODUCTIVE TOXICITY	2

PICTOGRAM(S)



Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been

Response:

read and understood. Wear protective gloves, clothing, eye and face protection.

IF exposed or concerned: Get medical attention.

Storage:

Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Boric acid	10043-35-3	0.1 - 1

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

IDH number; 530539

Product name: LePage® Carpenter's Glue

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. Get immediate

medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. Remove contaminated

clothing and footwear. Get immediate medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get immediate medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get immediate

medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material.

Special firefighting procedures: Firefighters should wear self-contained breathing apparatus. Water may be

ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme

heat. If water is used, fog nozzles are preferable.

Unusual fire or explosion hazards: None identified.

Hazardous combustion products: Smoke. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not allow material to

contaminate ground water system. Do not allow product to enter sewer or

waterways.

Clean-up methods: Keep unnecessary personnel away. Ensure adequate ventilation. Wear

appropriate protective equipment and clothing during clean-up. Dispose of

contaminated material as waste according to Section 13.

7. HANDLING AND STORAGE

Handling: Avoid breathing vapors or mists of this product. Use only in well-ventilated

areas. Wash thoroughly after handling.

Storage: Protect from freezing.

For Information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Boric acid	6 mg/m3 STEL Inhalable fraction. 2 mg/m3 TWA Inhalable fraction.	None	None	None

Engineering controls: Work should be done in an adequately ventilated area (i.e., ventilation

sufficient to maintain concentrations below one haif of the PEL and other relevant standards). Local exhaust ventilation is recommended when general

ventilation is not sufficient to control airborne contamination.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Observe OSHA regulations for respirator use (29 CFR 1910,134).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Opaque, Yellow Odor: Characteristic Odor threshold: Not available. pΗ: 4 - 5 Vapor pressure: 101.3 kPa

Boiling point/range: 100 °C (212°F) Melting point/ range: Not determined Specific gravity: 1.08

Vapor density:

Not determined Flash point: Not applicable Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not determined Flammability: Not applicable

Evaporation rate: 0.36 (Butyl acetate = 1) Solubility in water: Dispersible Partition coefficient (n-octanol/water): Not determined

VOC content: < 0.45 % (by weight) Viscosity: Not available. Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Normally stable.

Hazardous reactions: Will not occur.

Hazardous decomposition Smoke. Oxides of carbon.

products:

Incompatible materials: This product may react with strong acids, bases and oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

IDH number: 530539 Product name: LePage® Carpenter's Glue

Potential Health Effects/Symptoms

Inhalation:

May cause slight irritation.

Skin contact:

May cause mild skin irritation.

Eye contact:

May cause mild irritation

Ingestion:

May cause gastrointestinal tract irritation if swallowed. Not expected under normal conditions of

use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Boric acid	Oral LD50 (Mouse) = 3,450 mg/kg Oral LD50 (Rat) = 2,660 mg/kg Dermal LD50 (Rabbit) = > 2,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 0.002 mg/l	Behavioral, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Liver, Reproductive, Skin, Less weight gain and food intake.

Hazardous Component(s)	dous Component(s) NTP Carcinogen		OSHA Carcinogen (Specifically Regulated)
Boric acid	No	No	No

12. ECOLOGICAL INFORMATION

Ecological Information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division: Identification number: None None

Packing group:

None

IDH number; 530539 Product name: LePage® Carpenter's Glue

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by:

Jennifer Altman, Sr. Regulatory Affairs Specialist

Issue date:

08/01/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 530539

Product name: LePage® Carpenter's Glue

Page 5 of 5

	, ,			
	•			
			·	•
	·			

- ---